

Product data sheet

XP+

Low backlash planetary gearbox



| Gearbox data | |
|-------------------------|--------------------------|
| Designation: | XP030S-MF2-28-1G1-2S |
| Gearbox type | XP+ |
| Gearbox size | 030 |
| Design keyword | Standard |
| Gearbox variation | Motor attachment gearbox |
| Gearbox stages | 2 |
| Gearbox ratio i | 28 |
| Output design | Key |
| Clamping hub diameter | 24 mm |
| Gearbox backlash | Standard |
| Gearbox material number | 20028097 |

| Motor mounting parts (included in delivery) | |
|---|---------------------------------------|
| Incl. mounting parts for servo motor | TBD |
| Adapter plate | Configure with provided cymex® 5 file |

| Order designation |
|--|
| XP030S-MF2-28-1G1-2S / Specify your motor P/N here |

Confirm motor compatibility with cymex® 5. Download your pre-configured file and base 3D model here!^{d)}



| Technical specifications | | |
|---|--------------------|------------------------|
| Max. output torque (Depending on the specific boundary conditions of the application) | T _{2α} | 660 Nm |
| Max. acceleration torque (max. 1000 cycles per hour) | T _{2B} | 550 Nm |
| Nominal output torque (with n _{IN}) | T _{2N} | 287 Nm |
| Emergency stop torque (permitted 1000 times during the service life of the gearbox) | T _{2Not} | 1000 Nm |
| Nominal input speed (with T _{2N} and 20°C ambient temperature) ^{a)} | n _{1N} | 3100 min ⁻¹ |
| Max. input speed | n _{1Max} | 6500 min ⁻¹ |
| Mean no load running torque (with n ₁ =3000 min ⁻¹ and 20°C gearbox temp.) ^{b)} | T ₀₁₂ | 0.78 Nm |
| Max. torsional backlash | j _t | ≤ 4 arcmin |
| Torsional rigidity ^{b)} | C _{t21} | 45 Nm/arcmin |
| Tilting rigidity | C _{2K} | 675 Nm/arcmin |
| Max. axial force ^{c)} | F _{2AMax} | 6700 N |
| Max. radial force ^{c)} | F _{2RMax} | 9000 N |
| Max. tilting moment | M _{2KMax} | 1296 Nm |
| Efficiency at full load | η | 94 % |
| Service life (for calculation, see the Chapter "Information" in our product catalogue) | L _h | > 20000 h |
| Weight incl. standard adapter plate | m | 7.6 kg |
| Operating noise (with n ₁ =3000 min ⁻¹ no load) | L _{PA} | ≤ 57 dB(A) |
| Max. permitted housing temperature | | 90 °C |
| Ambient temperature | | -15 °C to 40 °C |
| Lubrication | | lubricated for life |
| Paint | | Innovation blue |
| Protection class | | IP 65 |
| Inertia (relates to the drive) | J ₁ | 1.98 kgcm ² |

a) For higher ambient temperatures, please reduce input speed



b) Depends on clamping hub diameter

c) Refers to center of the output shaft or flange





d) Use cymex® 5 to confirm adapter plate dimensions and motor compatibility

Don't have cymex® 5? Get your Premium license here!

New to cymex® 5? Learn how to check motor compatibility quickly with a simple tutorial.



Please note: adapter plate dimensions may vary based on specified motor



1) Motorwellenpassung pruefen / Check motor shaft fit

Technische Aenderungen vorbehalten / Technical modifications reserved

Betriebsanleitung unter www.wittenstein-alpha.de / Operating manual on www.wittenstein-alpha.de

Nicht tolerierte Masse sind Nennmasse / Non-toleranced dimensions are nominal dimensions

| | | | |
|--|--|------------------|--|
| gez/draft | | Masstab Scale | |
| Datum/date | | auto | |
| Eigentumsvorbehalt nach DIN 34 beachten ! | Observe copyright note according to DIN 34 ! | | |
| Benenn. Descr. | XP 030S-MF2- 28-1G1-2S | | |
| Kommentar Note | Motor specified by user - compatibility check required | | |
| MN | 20028097 | DIN A3 | Urspr./Ref-Drwg: CAD-Generator V2.0 Blatt/Sheet: 1 |



nicht vertraulich

This drawing is our intellectual property and is only issued for exclusively personal and confidential use. It may not be copied, reproduced, disclosed or made available to third parties in any form whatsoever without our written permission.

Diese Zeichnung ist unser geistiges Eigentum und wird nur zum ausschliesslich persönlichen, vertraulichen Gebrauch ausgehändigt. Sie darf ohne unsere schriftliche Genehmigung weder kopiert, noch vervielfältigt, noch in irgend einer Form Dritten Personen mitgeteilt oder zugänglich gemacht werden.

| Anbauteile / mounting parts | | |
|--------------------------------|----|-----|
| Adapterplatte adapter plate | MN | TBD |
| Distanzhülse bushing | MN | |