

# Product data sheet

**XP+**

Low backlash planetary gearbox



Gearbox data	
Designation:	XP030S-MF2-40-1E1-2S
Gearbox type	XP+
Gearbox size	030
Design keyword	Standard
Gearbox variation	Motor attachment gearbox
Gearbox stages	2
Gearbox ratio i	40
Output design	Key
Clamping hub diameter	19 mm
Gearbox backlash	Standard
Gearbox material number	20026692

Motor mounting parts (included in delivery)	
Incl. mounting parts for servo motor	TBD
Adapter plate	Configure with provided cymex® 5 file

Order designation	
XP030S-MF2-40-1E1-2S / Specify your motor P/N here	

Confirm motor compatibility with cymex® 5. Download your pre-configured file and base 3D model here!<sup>d)</sup>



Don't have cymex® 5? Get your Premium license here!



Technical specifications		
Max. output torque (Depending on the specific boundary conditions of the application)	T <sub>2α</sub>	660 Nm
Max. acceleration torque (max. 1000 cycles per hour)	T <sub>2B</sub>	550 Nm
Nominal output torque (with n <sub>IN</sub> )	T <sub>2N</sub>	319 Nm
Emergency stop torque (permitted 1000 times during the service life of the gearbox)	T <sub>2Not</sub>	1000 Nm
Nominal input speed (with T <sub>2N</sub> and 20°C ambient temperature) <sup>a)</sup>	n <sub>1N</sub>	3100 min <sup>-1</sup>
Max. input speed	n <sub>1Max</sub>	6500 min <sup>-1</sup>
Mean no load running torque (with n <sub>1</sub> =3000 min <sup>-1</sup> and 20°C gearbox temp.) <sup>b)</sup>	T <sub>012</sub>	0.56 Nm
Max. torsional backlash	j <sub>t</sub>	≤ 4 arcmin
Torsional rigidity <sup>b)</sup>	C <sub>t21</sub>	45 Nm/arcmin
Tilting rigidity	C <sub>2K</sub>	675 Nm/arcmin
Max. axial force <sup>c)</sup>	F <sub>2AMax</sub>	6700 N
Max. radial force <sup>c)</sup>	F <sub>2RMax</sub>	9000 N
Max. tilting moment	M <sub>2KMax</sub>	1296 Nm
Efficiency at full load	η	94 %
Service life (for calculation, see the Chapter "Information" in our product catalogue)	L <sub>h</sub>	> 20000 h
Weight incl. standard adapter plate	m	7.6 kg
Operating noise (with n <sub>1</sub> =3000 min <sup>-1</sup> no load)	L <sub>PA</sub>	≤ 56 dB(A)
Max. permitted housing temperature		90 °C
Ambient temperature		-15 °C to 40 °C
Lubrication		lubricated for life
Paint		Innovation blue
Protection class		IP 65
Inertia (relates to the drive)	J <sub>1</sub>	0.55 kgcm <sup>2</sup>

a) For higher ambient temperatures, please reduce input speed

b) Depends on clamping hub diameter



c) Refers to center of the output shaft or flange



d) Use cymex® 5 to confirm adapter plate dimensions and motor compatibility

New to cymex® 5? Learn how to check motor compatibility quickly with a simple tutorial.



This drawing is our intellectual property and is only issued for exclusively personal and confidential use. It may not be copied, reproduced, disclosed or made available to third parties in any form whatsoever without our written permission.



gez/draft		 Massstab Scale <b>auto</b>	 <b>WITTGENSTEIN</b>	<b>alpha</b>
Datum/date				
Eigentumsvorbehalt nach                      Observe copyright note DIN 34 beachten !                      according to DIN 34 !				
Benenn. <b>XP 030S-MF2- 40-1E1-2S</b> Descr.				
Kommentar <b>Motor specified by user - compatibility check required</b> Note				
MN	20026692	DIN A3	Urspr./Ref-Drwg:	CAD-Generator V2.0 Blatt/Sheet: 1

nicht vertraulich

Diese Zeichnung ist unser geistiges Eigentum und wird nur zum ausschliesslich persönlichen, vertraulichen Gebrauch ausgehendigt. Sie darf ohne unsere schriftliche Genehmigung weder kopiert, noch vervielfältigt, noch in irgend einer Form Drittpersonen mitgeteilt oder zugaenglich gemacht werden.